

System Impact Study SPP-2017-055 For Transmission Service Requested By: MCPI

From BLUECANYON2 to ERCOTN

For a Reserved Amount Of 220 MW From 04/04/2018 To 09/01/2018

SPP IMPACT STUDY (SPP-2017-055) December 8, 2017 1 of 6

<u>1. Executive Summary</u>

MCPI has requested a system impact study for monthly firm transmission service from BLUECANYON2 to ERCOTN. The period of the transaction is from 04/04/2018 00:00 to 09/01/2018 00:00. The request is for reservation 85984092.

The 220 MW transaction from BLUECAYON2 has an impact on the following flowgates with no AFC: SPSNORTH_STH. To provide the AFC necessary for this transfer, the impact on these flowgates must be relieved.

After studying many scenarios using generation redispatch, there are several feasible scenarios that will relieve the flowgate(s) in question.

2. Introduction

MCPI has requested a system impact study for transmission service from BLUECANYON2 to ERCOTN.

There are 1 constrained flowgates that require relief in order for this reservation to be accepted. The flowgates and the explanations are as follows:

- SPSNORTH_STH: SPS North – South Tie

3. Study Methodology

A. Description

Southwest Power Pool used Transmission Adequacy & Reliability Assessment (TARA) to obtain possible unit pairings that would relieve the constraint. TARA calculates impacts on monitored facilities for all units within the Southwest Power Pool Footprint. The SPP ATC Calculator is used to determine response factors for the time period of the reservation.

B. Model Updates

The 2017 Southwest Power Pool model was used for the study. This model was updated to reflect the most current information available.

C. Transfer Analysis

Using the short-term calculator, the limiting constraints for the transfer are identified. The response factor of the transfer on each constraint is also determined.

The product of the transfer amount and the response factor is the impact of a transfer on a limiting flowgate that must be relieved. With multiple flowgates affected by a transfer, relief of the largest impact may also provide relief of smaller impacts.

Using Transmission Adequacy & Reliability Assessment (TARA), specific generator pairs are chosen to reflect the units available for redispatch. The quotient of the amount of impact that must be relieved and the generation sensitivity factor calculated by TARA is the amount of redispatch necessary to relieve the impact on the affected flowgate.

4. Study Results

After studying the impacts of the request, one flowgate require relief. The flowgates and associated amount of relief are as follows:

Table 1

		Sensitivity	nsitivity Required Relief	
Flowgate	Duration	(%)	(MW)	
5196:SPSNORTH_STH	4/1/2018 00:00 - 9/1/2018 00:00	12.13%	27	

Table 2 displays a list of generator pairs that are possible relief options for each flowgates in question and the amount of redispatch capacity needed.

Table 2

5196:SPSNORTH_STH					
Increment	Decrement	Sensitivity	MW		
Plant X	Harrington	81.58%	33		
Plant X	Nichols	81.55%	33		
Tolk	Harrington	80.51%	34		
Tolk	Nichols	80.48%	34		
Cunningham	Harrington	79.05%	34		
Cunningham	Nichols	79.02%	34		
Plant X	Blackhawk	78.56%	34		
Tolk	Blackhawk	77.50%	35		
Cunningham	Blackhawk	76.03%	36		

5. Conclusion

Generation redispatch (and reservation curtailment) options were studied in order to relieve the necessary constraints. The results of this study shows that the constraints on the flowgates in question could be relieved by executing one or more of the options described in the Study Results section of this document. Before the Transmission Provider accepts the reservations, proof of the necessary relief options must be presented to Southwest Power Pool. Noncompliance with this guideline will result in the refusal of the reservation.